



公差/General tolerances(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±0.1
	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.45	±0.54	±0.63	±0.75	±0.90	±1.05	±1.15	±1.50	±2.50

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300V/1.5	/	300V/1.0
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	/	32.0/2.0	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	/	4	/
线径范围(硬线和软线)/Wire Range (rigid and flexible)(AWG/mm²)	22~14/0.2~2.5		
间距/Pitch(mm)/线径范围/Poles	5.08/N=02~24P		
剥线长度/Stripping Length(mm)	9~10		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number: PANTONE	PANTONE 428C		

7	Housing2	PA66	UL94V-0
6	Spring	Stainless Steel	/
5	Pin	Copper alloy	Sn Plated
4	Cover2	PA66	UL94V-0
3	Cover1	PA66	UL94V-0
2	Side Housing	PA66	UL94V-0
1	Housing1	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

Note: The A&Z (H) in the name means: A(H) and Z(H).

<b>DEGSON</b>		MATERIAL:	SURFACE/COLOR:
APPD:		MAT NO./REV:	/ 00
CMO:		MAT STATUS:	批量
DPT:			

REV	00	ECN		DESCRIPTION	DPT	DATE	DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
							200200463	CUSTOMER DRAWING	work	2:1	1/1