

## Overview

### Product information



## SA-EBC-2105-F-25030000002

Socket with cover to protect it .Rated current:50A; Rated voltage:110V DC;  
Withstand voltage:500V AC; Insulation resistance > 100M Ω; Protection grade  
meet IP67 for socket only; Mechanical life ≥ 3000 times; Pull out force > 25N;  
Operating temperature: - 40 ~ 105 ℃; Salt spray resistance : 72h; Flame  
retardant grade:UL94-v0; Environmental protection:RoHS.

### Product advantages

- ☑ The socket flap can effectively protect the plug-in interface
- ☑ High plug life
- ☑ Beautiful appearance, more in line with human functional design

### Product certification

# RoHS

## Technical data

### Product drawing

### 3D model

□

### Marking

classification	Insert
Series	DD
	DDD
	DM

### technical parameter

insulation resistance	≥100MΩ
Mechanical life	≥3000次

### versions

Connection method	Screw connection
Female/Male	Male
Dimension	3A
	32A
	6B
	10B
	24B
	32B
	48B
Number of positions	3
	2
	1

Environmental parameters

Degree of protection	MatchingIP67
----------------------	--------------

Accessories

Business data

Order number	25030000002
Packing unit	
Minimum order quantity	
Products weight (without packaging)	