

## Overview

### Product information



## SA-EBBL-2105-F-25050000005

Socket with direct plug in and out. Rated current: 50A; Rated voltage: 110V DC; Withstand voltage: 500V AC; Insulation resistance > 100M  $\Omega$ ; Protection grade meet IP67 for socket only; Mechanical life  $\geq$  3000 times; Pull out force > 25N; Operating temperature: - 40 ~ 105  $^{\circ}\text{C}$ ; Salt spray resistance : 72h; Flame retardant grade: UL94-v0; Environmental protection: RoHS.

### Product advantages

- ☒ Fast direct plug connection
- ☒ After plugging in place, it has auditory and visual feedback
- ☒ High plug life
- ☒ Beautiful appearance, more in line with human functional design

### Product certification

# RoHS

## Technical data

### Product drawing

### 3D model

☐

### Marking

classification	Insert
Series	DD
	DDD
	DM

### technical parameter

insulation resistance	$\geq 100\text{M}\Omega$
Mechanical life	$\geq 3000$ 次

versions

Connection method	Screw connection
Female/Male	Male
Dimension	3A
	32A
	6B
	10B
	24B
	32B
	48B
Number of positions	3
	2
	1

Environmental parameters

Degree of protection	MatchingIP67
----------------------	--------------

Accessories

Business data

Order number	25050000005
Packing unit	
Minimum order quantity	
Products weight (without packaging)	