

Overview

Product information

**Bus IO-DF750-HT-001-11-1001A(H)-30050000253**

Card IO housing,push-instructure,Can be matched bring light RJ45Connector,LEDinstruct

Product advantages

- ☑Dual network port without light RJ45 interface
- ☑8-bit address interface
- ☑Internal bus through bottom 6 gold-plated terminals
- ☑Equipped16aislePower Module ,LEDs per node
- ☑Internal 2 gold-plated blade connectors for power cascading expansion
- ☑Can be installed on DIN rail

Product certification

Technical data

Product drawing

3D model

□

Connection method (IO)

wiring

PUSH-IN wiring technology

Mechanical parameters

structure type

Compact terminal module housing with signal LED

Material

PC+PA66

installation

DIN35 rail

Side by side installation

Dovetail groove clamping

label

Laser screen printing

color

C1 gray

Environmental data

Ambient temperature (operation)	-40℃～+70℃
Ambient temperature (storage / transport)	-40℃～+70℃

Connection method(IO)

Strip length	8-9mm
Power contacts	2 blade contacts
Power load	10A
Rated current	Power: 24V Bus connector: 5V
Cross section	0.2~2.5mm ²
Connectable guide cross section AWG	28~12AWG
PCB thickness	1.0mm

Dimension

length	100mm
width	48mm
Height	69mm

Accessories

Business data

Order number	30050000253
Packing unit	20 SKT
Minimum order quantity	20 SKT
Products weight (without packaging)	122.5g