

Overview				
Product information				
The second	DGV10-1009000027 Through-wall terminal blocks, Rated current: 57A, Rated voltage (III/3) : 400V, width: 10.1mm, Color: glay, Contact surface :Tin			
Product advantages				
 Screw connection technology,safe and reliable Through-wall installation, free positioning 				
Product certification				
c FL [®] us				
Technical data Product drawing				
3D model				
 Connection capacity 				
Conductor cross section solid		0.5~16mm²		
Conductor cross section flexible		0.5~10mm ²		
AWG		24~6AWG		
Torque		1.2N.m		
Strip length		10mm		
Electrical parameters UL				
Rated voltage (B)		300V		
Rated voltage (C)		150V		
Rated voltage (D)		300V		

Rated current (B)	65A
Rated current (D)	10A
Rated current (C)	65A
Electrical parameters IEC	
Rated voltage(III/3)	400V
Rated current	400∨
	57A
Rated surge voltage(III/3)	бку
tem properties	
Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M4
Number of potentials	1
Pluggable or not	Yes
Number of rows	1
Material data	
Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	Ι
Flammability rating	UL94V-0
Mechanical tests	
Test Specification	UL1059/IEC60998

Environmental data

Ambient temperature (operation)

cessories	
pol	
screwdriver	0.8x4.0mm,Slotted screwdriver
Operating tool	/
ccessories	
Coding strip	1
Marking strip	ZB10
Bridge	EB xx-10
Other	/
ccessories	
Coding strip	/
Bridge	
Marking strip	ZB10
Others	/
ool	
Operating tool	1
Screwdriver	1.0x4.0mm, Slotted screwdriver

Business data	
Order number	1009000027
Packing unit	50
Minimum order quantity	

Products weight (without	
packaging)	