


Overview

Product information



DG212S-THR-5.0-10060001895

PCB spring terminal blocks, Rated current: 17.5A. Rated voltage
(III/2) : 320V, pitch: 5.0mm, Color: black, Contact surface : Tin

Product advantages

- ☒ PUSH-IN connection technology, fast wiring
- ☒ Suitable for THR welding process
- ☒ Universal installation method, suitable for various situations

Product certification



Technical data

Product drawing

3D model

□

Processing notes

Process

Reflow soldering/wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~1.5mm²

Conductor cross section flexible

0.2~1.5mm²

AWG

28~14AWG

Strip length

9mm

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)	12A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	320V
Rated voltage(III/3)	250V
Rated current	17.5A
Rated voltage(III/2)	320V
Rated voltage(II/2)	500V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection direction	45°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Quick connection
Pitch	5mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated

Contact zone metal surface	tin-plated
Insulation Materials	High temperature resistant materials
Shell color	Black
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL 1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40°C~130°C(depending on derating curve)
---------------------------------	--

Accessories

Business data

Order number	10060001895
Packing unit	1790
Minimum order quantity	
Products weight (without packaging)	1.52