

Overview

Product information



ESS-150A-35-B-BK-18-20160003061

Energy Storage Connector, Product range: ESS socket, Color: black, Wire cross section: 35 mm², Rated voltage: 1500V, Rated current: 150 A, Connection method: Busbar, Contact type: Needle

Product advantages

- ☑ Exclusive patents
- ☑ IP67 protection
- ☑ With safety locking latch
- ☑ The plug can rotate 360° after assembled
- ☑ The socket is with hand-proof protection
- $\ensuremath{\mbox{\sc W}}$ With color-coded and mechnism-coded desgin avoiding misplug

Product certification





Technical data

-		
Product	a	Irawına
1 TOGGC	u	naving

3D model

Wiring data

Wiring mode	Busbar
-------------	--------

Environment condition

Protection grade (pair plug)	IP67
Ambient temperature (operation)	-40°C ~ +125°C
Ambient temperature (storage/transportation)	-40°C ~ +80°C
Altitude	2000m

Mechanical properties

Plugging times	100
Pullout force	>10N
lechanical properties	
Insertion force	< 100N
tandards and specifications	
Standard/Specification	UL4128
laterial data	
Insulating material	Nylon
Halogen-free	Compliance with standards
Environmental protection matters	REACH/RoHS compliant
Sealing ring material	Silicone
Contact material	Copper alloy
Shell color	Black
Flammability rating	UL94V-0
lectrical parameters	
Pollution level	3
Rated current	150A
Nateu current	UL DC1500V
Insulation resistance	>5000ΜΩ
Contact resistance	≤0.5mΩ

Accessories

Business data	
Order number	20160003061

Packing unit	50
Minimum order quantity	50
Products weight (without packaging)	46