

Overview

Product information



ESS-120A-25-B-OR-00-20160000016

Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 25 mm², Rated voltage: 1500V, Rated current: 120 A, Connection method: Busbar, Contact type: Needle

Product advantages

- ☑ Exclusive patents
- ☑ IP67 protection
- ☑ With safety locking latch
- ☑ The plug can rotate 360° after assembled
- ☑ The socket is with hand-proof protection
- $\ensuremath{\mbox{\sc W}}$ With color-coded and mechnism-coded desgin avoiding misplug

Product certification





Technical data

-		
Product	a	rawina
1 TOGGC	u	i a wii ig

3D model

Wiring data

Wiring mode	Busbar
-------------	--------

Environment condition

Protection grade (pair plug)	IP67
Ambient temperature (operation)	-40°C ~ +125°C
Ambient temperature (storage/transportation)	-40°C ~ +80°C
Altitude	2000m

Mechanical properties

Plugging times	100
Insertion force	<60N
Pullout force	>10N
Standards and specifications	
Standard/Specification	UL4128
Material data	
Insulating material	Nylon
Halogen-free	Compliance with standards
Environmental protection matters	REACH/RoHS compliant
Sealing ring material	Silicone
Contact material	Copper alloy
Shell color	Orange

Electrical parameters

Flammability rating

Pollution level	3
Rated current	120A
	UL DC1500V
Insulation resistance	>5000MΩ
Contact resistance	≤0.5mΩ

UL94V-0

Accessories

Business	data
Dusiliess	uala

Order number	20160000016
Packing unit	32

Minimum order quantity	50
Products weight (without packaging)	27