

## Overview

### Product information



## Bus IO-DF750-001-11-2001A(H)-30050000129

Card type IO shell,can be equipped with RJ45 connector,LED indicator

### Product advantages

- ☑ Dual network ports without lights RJ45 interface
- ☑ 8-bit address interface
- ☑ Internal bus through 6 gold-plated terminals at the bottom
- ☑ Equipped with 8 channels power module, each node is equipped with LED
- ☑ Two internal gold-plated blade connectors are used for power cascade expansion
- ☑ Can be installed on DIN rail

### Product certification

## Technical data

### Product drawing

### 3D model

□

### Dimension

|        |        |
|--------|--------|
| width  | 48mm   |
| Height | 69mm   |
| length | 93.5mm |

### Mechanical parameters

|                           |                                                 |
|---------------------------|-------------------------------------------------|
| structure type            | Compact terminal module housing with signal LED |
| Material                  | PC+PA66                                         |
| installation              | DIN35 rail                                      |
| Side by side installation | Dovetail groove clamping                        |

|       |                       |
|-------|-----------------------|
| label | Laser screen printing |
| color | C1 gray               |

#### Environmental data

|                                           |           |
|-------------------------------------------|-----------|
| Ambient temperature (operation)           | -40℃～+70℃ |
| Ambient temperature (storage / transport) | -40℃～+70℃ |

#### Connection method(IO)

|                                     |                               |
|-------------------------------------|-------------------------------|
| wiring                              | Spring type wiring technology |
| Strip length                        | 8-9mm                         |
| Power contacts                      | 2 blade contacts              |
| Power load                          | 10A                           |
| Rated current                       | Power: 24V Bus connector: 5V  |
| Cross section                       | 0.2~2.5mm <sup>2</sup>        |
| Connectable guide cross section AWG | 28~12AWG                      |
| PCB thickness                       | 1.0mm                         |

#### Accessories

##### Accessories

|            |                       |
|------------|-----------------------|
| IO housing | DF750-200-11-2001A(H) |
|------------|-----------------------|

#### Business data

|                                     |             |
|-------------------------------------|-------------|
| Order number                        | 30050000129 |
| Packing unit                        | 20          |
| Minimum order quantity              | 20          |
| Products weight (without packaging) | 122.5       |

