

Overview

Product information



D48B-SF-1L-CV-2PG29-21010000588

48B Lower base,single buckle,back cover ,side entry,double PG29 Thread hole,Wear protective cover

Product advantages

- ☑Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- ☑Various installation methods and outlet directions to meet on-site wiring requirements;
- ☑Snap-in combination structure, dustproof, waterproof, easy operation;

Product certification

Technical data

Product drawing

3D model

□

Marking

| | |
|----------------|-------------------------|
| classification | Upper Housing/base |
| Series | B |
| Type | Surface mount base |
| Description | With plastic dust cover |
| Specification | Low structure |

versions

| | |
|----------------------|-------------|
| Dimension | 48B |
| locking Category | Single lock |
| Thread specification | 2x PG29 |

Material characteristics

| | |
|-------------------------------|--------------------------|
| Flammability rating | V-0 |
| RoHS | conform |
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base) | spray |
| Color (upper housing/base) | Grey (RAL 7037) |
| Material (seal) | NBR |
| Material (lock catch) | Stainless steel |

Technical specification

| | |
|-----------------------|------------|
| Limiting temperatures | -40℃~+125℃ |
| IP class | IP65 |

Accessories

Business data

| | |
|-------------------------------------|-------------|
| Order number | 21010000588 |
| Packing unit | 100 |
| Minimum order quantity | 1 |
| Products weight (without packaging) | 1830 |