

Overview

Product information



D10B-SF-1L-M25-21010000216

10B Lower base, single buckle, back cover , side entry, M25 Thread hole

Product advantages

☑Metal or high-strength plastic material, resistant to high-strength mechanical shock;

☑Various installation methods and outlet directions to meet on-site wiring requirements;

 $\ensuremath{\square}$ Snap-in combination structure, dustproof, waterproof, easy operation;

Product certification

Technical data

Product drawing

3D model

Marking

| classification | Upper Housing/base |
|----------------|--------------------|
| Series | В |
| Туре | Surface mount base |
| Specification | Low structure |

versions

| Dimension | 10B |
|----------------------|-------------|
| locking Category | Single lock |
| Thread specification | 1x M25 |

Material characteristics

| Flammability rating | V-0 | |
|-------------------------------|--------------------------|--|
| RoHS | conform | |
| Material (upper housing/base) | Die-cast aluminium alloy | |
| Material(upper housing/base) | spray | |
| Color (upper housing/base) | Grey (RAL 7037) | |
| Material (seal) | NBR | |
| Material (lock catch) | Zinc plated | |
| echnical specification | | |
| Limiting temperatures | -40℃~+125℃ | |
| IP class | IP65 | |

| Accessories | | | |
|-------------|--|--|--|
| | | | |

| Business data | |
|-------------------------------------|-------------|
| Order number | 21010000216 |
| Packing unit | 100 |
| Minimum order quantity | 1 |
| Products weight (without packaging) | 229.2 |