

## Overview

### Product information



**D32A-BK-4g-21010000374**

32A Lower base, Four levers, no back cover

### Product advantages

- ☑ Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- ☑ Various installation methods and outlet directions to meet on-site wiring requirements;
- ☑ Snap-in combination structure, dustproof, waterproof, easy operation;

### Product certification

## Technical data

### Product drawing

### 3D model

□

### Marking

|                |                    |
|----------------|--------------------|
| classification | Upper Housing/base |
| Series         | A                  |
| Type           | Hole mounting base |
| Specification  | Low structure      |

### versions

|                  |             |
|------------------|-------------|
| Dimension        | 32A         |
| locking Category | Double lock |

### Material characteristics

|                     |     |
|---------------------|-----|
| Flammability rating | V-0 |
|---------------------|-----|

|                               |                          |
|-------------------------------|--------------------------|
| RoHS                          | conform                  |
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base)  | spray                    |
| Color (upper housing/base)    | Grey (RAL 7037)          |
| Material (seal)               | NBR                      |

Technical specification

|                       |            |
|-----------------------|------------|
| Limiting temperatures | -40℃~+125℃ |
| IP class              | IP65       |

Accessories

Business data

|                                     |             |
|-------------------------------------|-------------|
| Order number                        | 21010000374 |
| Packing unit                        | 100         |
| Minimum order quantity              | 1           |
| Products weight (without packaging) | 86          |