

Overview

Product information



D16B-TE-2L-M25-21010000314

16BHoods,double button,top entry,M25 Thread hole

Product advantages

 ${\bf \ensuremath{\square}} {\sf Metal} \ {\sf or} \ {\sf high-strength} \ {\sf plastic} \ {\sf material}, \ {\sf resistant} \ {\sf to} \ {\sf high-strength} \ {\sf mechanical} \ {\sf shock};$

☑Various installation methods and outlet directions to meet on-site wiring requirements;

 $\ensuremath{\square}$ Snap-in combination structure, dustproof, waterproof, easy operation;

Product certification

Technical data

Product drawing

3D model

Marking

classification	Upper Housing/base
Series	В
Туре	Top housing
Specification	Low structure

versions

Dimension	16B
locking Category	Double lock
Wiring method	Top entry
Thread specification	1x M25

Material characteristics

RoHS	conform
Material (upper housing/base)	Die-cast aluminium alloy
Material(upper housing/base)	spray
Color (upper housing/base)	Grey (RAL 7037)
Material (lock catch)	Zinc plated

Technical specification

Limiting temperatures	-40℃~+125℃
IP class	IP65

Accessories

Business data

Order number	21010000314
Packing unit	100
Minimum order quantity	1
Products weight (without packaging)	221.6