


Overview

Product information

**PC16-PE-11010000028**

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 16 mm², AWG: 12 - 4, Width: 12.2 mm, Color: green-yellow, Mounting type: NS 35/7.5, NS 35/15

Product advantages

- ✓ Screw connection technology, reliable connection;
- ✓ Grounding structure, protection circuit;
- ✓ Copper alloy material, good corrosion resistance;
- ✓ Can be matched with marker strips to avoid incorrect insertion of wires.

Product certification



Technical data

Product drawing

3D model

[□](#)

Overview

Number of rows	1
number of connections	2
Open-end side panels	no
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0
Insulating material group	I
standard test	IEC60947-7-2
Connection method	screw connection

Dimension	
width	12.2mm
End plate width	/
Height	52.8mm
NS 35/7,5 Height	54mm
NS 35/15 Height	61.5mm
length	42.5mm
Wiring data	
Strip length	11~12mm
Conductor cross section solid AWG	12~4
Conductor cross section solid	0.2~16mm ²
Conductor cross section flexible	0.2~16mm ²
Conductor cross section flexible (ferrule with plastic sleeve)	0.2-16mm ²
Screw type	Slotted screw
screw thread	M4
Tightening torque	1.2N.m
IEC Electrical parameters	
Rated voltage (III / 3)	/
Rated current (III / 3)	/
IEC Electrical parameters	
Rated surge voltage	8KV
UL Electrical parameters	
Rated voltage	/
Rated current	/
Environmental conditions	

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%
Ambient temperature (storage / transport)	-25°C~60°C

Mechanical performance test

Mechanical strength	Passed the test
Fixing support	Passed the test
Rotational Pull Test	Passed the test

Electrical performance test

Voltage drop	≤3.2mV
Temperature rise test	≤45 K

Safety test

Anti-finger touch	Passed the test
-------------------	-----------------

Environmental protection

RoHS	No excessive harmful substances
REACH SVHC	Lead 7439-92-1

Accessories

Accessories

Slotted screwdriver size (Blade thickness x Width)	1×4
Fixed bridge	/
Insertion bridge	EB2-12 / EB3-12 / EB10-12
End cover	/
Separating disk	/
Partition plate	/

Marker

Top marker	/
Marker	ZT12
Marker support	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Marking & Installation

Marking strip	ZB10
Marker cards	DBE-1

Accessories

Bridge	EBXX-12
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

Business data

Order number	11010000028
Packing unit	50
Minimum order quantity	50
Products weight (without packaging)	35.36