

Overview				
Product information				
		5P-MM-SH8002-20030001191 male socket,M12,Coding B,Front panel installation/M16*1.5 oldering cup		
Product advantages				
 Sealing optimization, protection level up to IP68 Meet the harsh environment Suitable for various occasions connection technology Compatible with the international and domestic same series products 				
Product certification				
CSAN [®] US ROHS	REACH of			
Technical data				
Product drawing				
3D model				
•				
Environmental conditions				
Ambient temperature		-40℃105℃		
Ambient temperature		-40℃105℃ IP68		
IP class				
IP class		IP68		
IP class General parameters		IP68 4A		
IP class General parameters Rated current		IP68 4A 60V		

Overvoltage level	Π
Pollution level	3
Connection method	Soldering
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm
Type of installation	Installation in front of the board

Material

Flammability rating ,in line with UL94	VO	
Contact material	CuZn	
Material contact surface	Au	
Contact carrier material	PA	
Coil material	Zinc alloy, nickel plated	
Sealing material	Silicon	
Standards and specifications		
Standards/specifications	IEC 61076-2-101	

Accessories	
Accessories	
Sealing cap	CAP-M12-FP-8003

Business data		
Order number	20030001191	
Packing unit	/	
Minimum order quantity	100	
Products weight (without packaging)	1	