

### Overview

#### Product information



## PM-M12S-04P-FF-SR8B01-20030000842

Sensor/Actuator Cable, PUR, black, UL20549, Female plug, acodado M12, Coding S, Unshielded, Trimming cable end, Cable Length: 1m

### Product advantages

☑ Sealing optimization, protection level up to IP68

☑Meet the harsh environment

☑Suitable for various occasions connection technology

 $\ensuremath{\square}$  Compatible with the international and domestic same series products

Product certification

Rated current

Number of potentials

Insulation resistance

Error-proof coding

# ROHS REACH

Product drawing		
BD model		
Environmental conditions		
Ambient temperature	-25℃80℃	
IP class	IP68	

12A

630V

≥ 100 MΩ

S-Code

4

Overvoltage level	III
Pollution level	3
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm

## Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PU
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

### Standards and specifications

Standards/specifications	IEC 61076-2-111	

## Cable

Cable type	PUR Black
Cable type(abbreviation)	PUR
UL AWM form	UL20940
Cross section	1.31 mm²
AWG signal wire	16AWG
Wire structure Signal wire	26/0.254mm²
Core diameter (including insulation layer)	3.1±0.05mm
Wire color	1 Black1 2 Black2 3 Black3 PE Yellow/Green
Thickness, insulation	0.68mm
Cable outer diameter D	9.2mm
Minimum bend radius ,fixed installation	5*OD

Minimum bend radius ,mobile installation	10*OD
Bending times	2 million times
Bending radius	50.8mm
Cable weight	136kg/km
Outer sheath, material	PU
Conductor insulation material	PVC
Conductor material	Tinned copper
Insulation resistance	10ΜΩ
Conductor resistance	Maximum 14.6Ω/km (at 20 °C) )
Nominal cable voltage	1000V
Cable test voltage	2000V
Special attributes	Silicone-free
Flame retardant	VW-1
Other protection functions	Anti-UV
Dimension	

Accessories		
Accessories		
Sealing cap	CAP-M12-MP-8001	

1m

Cable length

Business data	
Order number	20030000842
Packing unit	I .
Minimum order quantity	100

Products weight (without / packaging)