

Overview

Product information



PM-M12T-04P-FF-SR8A01-20030000849

Sensor/Actuator Cable,PVC,black,UL2517,Female plug,acodado M12,Coding T,Unshielded,Trimming cable end,Cable Cable length:1m

Product advantages

- ☑ Sealing optimization, protection level up to IP68
- ☑ Meet the harsh environment
- ☑ Suitable for various occasions connection technology
- ☑ Compatible with the international and domestic same series products

Product certification

RoHS REACH

Technical data

Product drawing

3D model

□

Environmental conditions

Ambient temperature

-25℃...80℃

IP class

IP68

General parameters

Rated current

12A

63V

Number of potentials

4

Insulation resistance

≥ 100 MΩ

Error-proof coding

T-Code

Overvoltage level	III
Pollution level	3
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PU
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-111
--------------------------	-----------------

Cable

Cable type	PVC Black
Cable type(abbreviation)	PVC
UL AWM form	UL2464
Cross section	1.31mm ²
AWG signal wire	16AWG
Wire structure Signal wire	26/0.254mm ²
Core diameter (including insulation layer)	2.3±0.05mm
Wire color	1 Brown 2 White 3 Blue 4 Black
Thickness, insulation	0.68mm
Cable outer diameter D	7.8mm
Minimum bend radius ,fixed installation	5*OD

Minimum bend radius ,mobile installation	10*OD
Bending radius	50.8mm
Cable weight	105.5kg/km
Outer sheath, material	PVC
Conductor insulation material	PVC
Conductor material	Tinned copper
Insulation resistance	10MΩ
Conductor resistance	Maximum 14.6Ω/km (at 20 °C)
Nominal cable voltage	300V
Cable test voltage	2000V
Special attributes	Silicone-free
Flame retardant	VW-1
Other protection functions	Anti-UV

Dimension

Cable length	1m
--------------	----

Accessories

Accessories

Sealing cap	CAP-M12-MP-8001
-------------	-----------------

Business data

Order number	20030000849
Packing unit	/
Minimum order quantity	100
Products weight (without packaging)	/

