

## Overview

### Product information



### DGR40-10A(H)-12010000157

Transfer barrier terminal blocks, Rated current: 60A. Rated voltage (UL) : 600V, Cross section: 22~6AWG, pitch: 14.0mm, Color: black, Contact surface: Tin

### Product advantages

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ Provide the cabinet and panel electrical transfer connections

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Connection capacity

AWG

22~6AWG

### Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	60A
Rated current (D)	5A
Rated current (C)	60A

### Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M5
Pitch	14mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40°C~125°C (depending on derating curve)
---------------------------------	---

Accessories

Accessories

--	--

Business data

Order number	12010000157
Packing unit	3
Minimum order quantity	/
Products weight (without packaging)	69.5