

Overview

Product information



FMET-04P-13020000116

DIN rail housings, Complete housing with metal foot catch,tall design, with vents, Width: 22.7mm, Unable to compatible bus connector,color:green,material:PA66,Flammability rating :V0,IP class:IP20.

Product advantages

- ☒ Modular design
- ☒ Multiple connection technologies optional, signal, data,and power transmission can be realized
- ☒ bus connector is optional
- ☒ Various personalized solutions can be achieved according to customer needs

Product certification

Technical data

Product drawing

3D model

□

Dimensions

| | |
|---------------------------------|---------|
| width | 22.7mm |
| length | 99.7mm |
| Height | 114.7mm |
| Depth from top edge of DIN rail | 107.7mm |

PCB data

| | |
|-------------------------|--------------------------------|
| Number of PCB holders | 2 |
| PCB thickness | 1.8mm |
| Installation location | Vertical (horizontal DIN rail) |
| PCBType of installation | Latching |

Item properties

| | |
|---------------------------|------------------|
| IP class | IP20 |
| Connection levels | 2(Both sides) |
| with ventilation openings | Yes |
| Maximum connection | 16 (pitch 5.0mm) |

Material data

| | |
|---------------------|-------|
| color | green |
| Material | PA66 |
| Flammability rating | V0 |

Environmental data

| | |
|---|--------------|
| Ambient temperature (assembly) | -5℃ ~ +105℃ |
| Ambient temperature (operation) | -40℃ ~ +105℃ |
| Ambient temperature (storage / transport) | -40℃ ~ +55℃ |

Accessories

Accessories

| | |
|------------|--------------------------|
| PCB Plug | 2EDGKF-5.0-04P-14-00A(H) |
| PCB Socket | 2EDGLF-5.0-04P-14-00A(H) |

Business data

| | |
|-------------------------------------|-------------|
| Order number | 13020000116 |
| Packing unit | 22 |
| Minimum order quantity | 22 |
| Products weight (without packaging) | 56.8 |

