


## Overview

### Product information



## DG238-10.0-10060000985

PCB spring terminal blocks, Rated current: 24A. Rated voltage  
(III/2) : 450V, pitch: 10.0mm, Color: White, Contact surface : Tin

### Product advantages

- ☒ Multiple wiring holes for current distribution
- ☒ Panel mounting, suitable for various situations
- ☒ Can realize horizontal wire-to-wire connection

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Connection capacity

AWG	22~14AWG
Strip length	9mm

### Electrical parameters UL

Rated voltage (B)	600V
Rated current (B)	20A

### Electrical parameters IEC

Rated current	450V
	24A
Rated voltage(III/2)	450V

Rated power frequency voltage(1min)	2.5KV
-------------------------------------	-------

#### Item properties

Connection method	Push-in spring connection
Pitch	10mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-2

#### Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

#### Environmental data

Ambient temperature (operation)	-40℃~105℃(depending on derating curve)
---------------------------------	--

#### Accessories

##### Accessories

Coding strip	/
Bridge	/
Marking strip	/

Others	/
--------	---

Tool

Operating tool	/
Screwdriver	/

Business data

Order number	10060000985
Packing unit	100
Minimum order quantity	30
Products weight (without packaging)	6.25