

#### Overview

#### **Product information**



# 2EDGKRM-5.08-10010002775

Pluggable terminal blocks,Rated current:20A.Rated voltage (III/2):250V,pitch:5.08mm,Color:green,Contact surface:Tin

#### Product advantages

- $\ensuremath{\mbox{$\sc\sc{Z}$}}$  Adapt to multi-type plugs, device design is highly flexible
- ☑ Keying parts can be installed
- ☑ Universal installation method, suitable for various situations

Product certification



#### Technical data

# Product drawing

3D model

## Connection capacity

Conductor cross section solid	1.0~2.5mm²
Conductor cross section flexible	1.0~2.5mm²
AWG	28~12AWG
Torque	0.4N.m
Strip length	7mm

## Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A

	Rated current (D)	10A
--	-------------------	-----

## Electrical parameters IEC

Rated voltage	250V
Rated current	20A
Rated voltage(III/2)	250V
Rated surge voltage(III/2)	2KV

# Item properties

Connection direction	0°
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M2.5
Pitch	5.08mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

## Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

## Mechanical tests

Test Specification	IEC61984/ UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C(depending on derating curve)

cessories	
ool	
Screwdriver	0.6x3.5, Slotted screwdriver
Operating tool	1
ccessories	
Coding strip	2EDG-PWP
Bridge	DG019-5.0
Marking strip	/
Others	1

usiness data	
Order number	10010002775
Packing unit	100
Minimum order quantity	30
Products weight (without packaging)	4.37